

**KOBELCO**

# Hydraulic Crawler Crane


# 7150

Max. Lifting Capacity: **150** Metric Tons at **5** MetersMax. Total Length (Boom+Luffing Jib): **99.36** Meters

## Specifications

- Advanced winch system delivers a wide range of precisely controlled hoisting speeds, and the fastest hoisting in its class.
- Large main and auxiliary drums can be run simultaneously or independently, at different speeds and in opposite directions, according to your needs.
- Two-speed propel system features high speed for travel, low for superior break-out force.
- Precise swing speed control allows for delicate inching operations.
- Direct fuel injection in an intercooled turbo engine delivers dependable performance with top fuel economy.

## General Dimensions



# Specifications

## Upper machinery



### Power plant

**Model** ..... Mitsubishi 6D22-TC  
**Type** ..... Water-cooled, direct fuel injection, intercooled turbo

**No. of cylinders** ..... 6  
**Bore and stroke** ..... 130 mm x 140 mm (5.1" x 5.5")  
**Displacement** ..... 11.1 liters  
**Rated power** ..... 294 ps (216 kW) at 2,000 rpm (JIS D1005)  
285 PS (210 kW) at 2,000 rpm (DIN 6270)  
275 HP (205 kW) at 2,000 rpm (SAE J 816b)  
**Max. torque** ..... 117 kg-m at 1,400 rpm (JIS D2005)  
**Cooling system** ..... Liquid, recirculating bypass  
**Starter** ..... 24V, 5.5kW  
**Generator** ..... 24V, 1.5kW  
**Cycles** ..... 4  
**Radiator** ..... Vertical tube and fin type core, thermostatically controlled  
**Air cleaner** . Dry type with replaceable paper element  
**Fuel tank capacity** ..... 400 liters (105 gal)  
**Batteries** ..... Two 12V, 200A-hr capacity batteries, series connected  
**Fuel consumption** (at 1,400rpm) ..... 154 gr/ps.hr



### Hydraulic system

**Pumps:** All four variable displacement pumps are driven by heavy-duty pump drive. One of these pumps is used in the right propel circuit and hook hoist circuit. Another is used in the left propel circuit and hook hoist circuit, and can accommodate an optional 3rd hoist circuit. The third is used in the boom hoist circuit, and the fourth variable displacement pump is used in the swing circuit. In addition, two gear pumps are used in the control system. One of these serves the clutch and brakes. The second pump can be used at the operator's discretion for a translifter, a cylinder for gantry lift, or a cylinder for boom foot pin or axlepin coupling and decoupling.

**Control:** Full-flow hydraulic control system for infinitely variable pressure to front and rear drums, boom hoist brakes and clutches. Controls respond instantly to the touch, delivering smooth function operation.  
**Pressure:** 280kg/cm<sup>2</sup> (3,980psi) maximum relief valve pressure

Load hoist, boom hoist and propel system ..... 280 kg/cm<sup>2</sup> (4,000 psi)  
Swing system ..... 230 kg/cm<sup>2</sup> (3,290 psi)  
Control system ..... 60 kg/cm<sup>2</sup> (860 psi)  
Hoist drum service brake system ..... 60 kg/cm<sup>2</sup> (860 psi)

**Reservoir capacity:** 500 liters (132 US gal)  
**Cooling:** Oil-to-air heat exchanger  
**Filtration:** Full-flow and bypass type with replaceable paper element



### Boom hoisting system

Powered by a hydraulic axial piston motor through a planetary reducer.

**Brake:** A spring-set, hydraulically released multiple-disc brake is mounted on the boom hoist motor and operated through a counter-balance valve.

Safety pawls (external ratchet) are fitted for locking the drums.

**Drums:** Two in-line drums, each grooved for 20mm (0.79") wire rope.

**Line speed:** Single line on first drum layer

Hoisting (max.) ..... 25 m/min (each)  
Lowering (max.) ..... 25 m/min (each)



### Load hoist system

Powered by two hydraulic axial piston motors, driven through a planetary reducer.

**Clutches:** Internally expanding band clutches.

**Brakes:** Externally contracting band brakes, each using positive and negative actuation.

**Drums** (front and rear): 588 mm (23") P.D. x 864 mm (34") wide drums, each grooved for 26 mm (1.02") wire rope. Rope capacity of 370m (1,213') working length and 490m (1,607') storage length.

**Line speed:** Single line on the first drum layer

Hoisting ..... 90/60/45/30 m/min  
Lowering ..... 90/60/45/30 m/min



### Swing system

**Swing unit:** Powered by dual hydraulic axial piston motors driving spur gears through planetary reducers, the swing system provides 360° rotation.

**Swing speed** ..... 2.2/1.1 rpm

**Swing brakes:** A spring-set, hydraulically released multiple-disc brake is mounted on each swing motor.

**Swing circle:** Single-row ball bearing with an integral internally cut swing gear.

**House lock:** Four position pin-in-hole lock (manually engaged)



### Operator's cab

Totally enclosed, full-vision cab fitted with safety glass and a sliding front window. A fully adjustable, high-backed seat permits operators to set their ideal working position. A signal horn, cigarette lighter, windshield wiper and inspection lamp socket are standard features.



### Controls

In front of the operator are foot pedals for front and rear drum brakes. At the operator's right are console-mounted adjustable short levers for front and rear drum control, boom hoist control lever and positive/negative brake select switch for front and rear drum brakes. Beside the operator's seat on the right are two short levers for propel control. At the operator's left are: a console-mounted swing lever, an optional third drum control lever, and front and rear drum pawl control switches; switches for ignition, engine stop, low and high speed control for front drum, rear drum and propel; and creep speed control for hoist and propel. A swing brake switch and a signal horn button are on the swing lever.

**Gauges:** Fuel, engine water temperature, engine oil pressure, hour meter.  
**Warning lamps:** Engine oil pressure, hydraulic oil pressure, battery charge, air cleaner and engine oil filter.

**Safety devices:** Hook over-hoist alarm and shut-off switch, boom over-hoist limit switch, boom angle indicator, signal horn, boom hoist and front and rear drum locks, swing lock, boom back stop, hook safety latch and optional load moment limiter (overload protection device) are provided.



**Gantry**

Folding type, fitted with sheave frame for boom hoist reeving. Lowers toward rear onto cab roof. Hydraulic lift is standard. Full up, full down positions with linkage.

**Counterweight**

Five-piece stack, mounted behind the machinery compartment.  
Total weight..... 54,000kg (119,000lb)



**Tools**

Tool set and accessories for routine machine maintenance are provided.

**Lower machinery**

**Carbody:** Steel-welded carbody with an integral seat designed for pin-connected axles.

**Crawler:** Crawler assemblies designed with a quick disconnect feature that allows complete individual removal from the axles. Crawler belt tension is maintained by hydraulic jack force on the track-adjusting bearing block.

**Crawler drive:** Independent hydraulic propel drive is built into each side frame, each with a hydraulic motor propelling a driving tumbler through a planetary gear box.

**Crawler brakes:** Spring-set, hydraulically released multiple-disc parking brakes are built into each propel drive.

**Steering mechanism:** A hydraulic propel system provides both skid steering (driving one track only) and counter-rotating steering (driving tracks in opposite directions).

**Track rollers:** 12 lower rollers and 2 upper rollers are fitted to each side frame, all permanently sealed and maintenance-free.

**Shoes:**

Number ..... 62 each side  
Standard flat shoe width ..... 1,070mm (42")  
(optional extra 1,220mm (48"))

**Max. travel speed:**

High range ..... 1.2km/h (0.75mph)  
Low range ..... 0.6km/h (0.37mph)

**Max. gradeability:** 30%

**Carbody counterweight (optional)**

A two-piece carbody counterweight and an additional counterweight can be optionally specified for mounting on the carbody to increase lifting capacity.

**Carbody counterweight** ..... 20,000kg (44,100lb)  
**Additional counterweight** ..... 8,300kg (18,300lb)

**Trans-Lifter (optional):** Trans-Lifter system allows quick and easy crawler side frame removal and trailer loading. 4 vertical cylinders lift the basic machine for self-loading onto trailer. 2 horizontal cylinders facilitate side frames for removal or replacement.

**Crane attachment**



**Boom:**

Welded lattice construction using tubular, high-tensile steel cords with pin connections between sections.

Max. lifting capacity	150,000kg (330,000lb)
Basic boom length	18.29m (60')
Max. boom length	82.30m (270')



**Jib (optional):**

Welded lattice construction using tubular, high-tensile steel cords with pin connections between sections.

		Fixed jib	Luffing jib
Max. lifting capacity	(kg)	15,000	20,000
Max. jib length	(m)	30.48	45.72
Max. total length (Boom length + jib length)	(m)	73.15 + 30.48	53.64 + 45.72



**Hook blocks**

A range of hook blocks can be specified, each with a safety latch.

	150tons	65 tons	25 tons	12 tons
Lifting capacity				
No. of sheaves	7	3	1	0
Weight (kg)	2,200	1,100	700	450

**Diameter of wire ropes**

**Standard:**

Hook hoist ..... 26mm (1.02")  
Boom hoist (16-part line) ..... 20mm (0.79")  
Boom pendants (4-part line) ..... 32mm (1.26")

**Optional:**

Jib hook hoist ..... 26mm (1.02")  
Jib back stay pendants (2-part line) ..... 26mm (1.02")  
Boom midpoint suspension ..... 22mm (0.08")

**Weight**

**Working weight:** Approx. 150,000kg (330,000lb)  
(including 18.29m (60ft) boom and 150ton hook block)  
**Ground pressure:** 0.93kg/cm<sup>2</sup> with 1,070mm (42") shoes.


# Lifting Capacities

The following points should be kept in mind when interpreting the ratings given below.

1. Operating radius is the horizontal distance from center of rotation to the hoist load line or tackle with load applied.
2. Rated loads do not exceed 75% of tipping loads, and include weights of the load, hook blocks, slings and other lifting devices.
3. Rated loads are for stationary and level cranes lifting a freely suspended load, and have been determined for ideal operating conditions. The user must limit or derate lifted loads to allow for adverse conditions (such as soft or uneven ground, out-of-level conditions, winds, side loads, pendulum action, jerking or sudden stopping of loads, inexperience of personnel, multiple machine lifts and traveling with a load.)
4. Gantry must be in fully raised position for all operations.
5. Crawlers must be fully extended and be locked in position.
6. The crane must be leveled to within 1% on a firm supporting surface.
7. When lifting over boom point with auxiliary sheave, rated loads for the boom must be deducted 450 kg.
8. Midpoint suspensions are required for booms 64.01 m (210') and longer.

9. Boom lengths for jib mounting are 45.72 m (150') to 73.15 m (240').
10. The boom should be erected over the front of the crawlers, not laterally.
11. At radii and boom length where no ratings are shown on-plate operation is not intended or approved.
12. Mast required when boom length is 60.96 m (200') or longer.
13. Boom insert and guy cables must be arranged as shown in the "Owner and Operator's Manual."
14. Lifting capacities shown within the heavy lines are limited by the strength of the boom.
15. Do not operate the machine with loads that exceed those shown.

## Working Ranges (with fixed jib)



## Boom Component Chart

Boom length m (ft)	Boom arrangement
18.29 (60)	Base-Tip
21.34 (70)	Base-A-Tip
24.38 (80)	Base-B-Tip
27.43 (90)	Base-C-Tip
30.48 (100)	Base-A-C-Tip
33.53 (110)	Base-B-C-Tip
36.58 (120)	Base-A-B-C-Tip
39.62 (130)	Base-A-C-C-Tip
42.67 (140)	Base-B-C-C-Tip
45.72 (150)	Base-C-C-C-Tip
48.77 (160)	Base-A-C-C-C-Tip
51.82 (170)	Base-B-C-C-C-Tip
54.86 (180)	Base-A-B-C-C-C-Tip
57.91 (190)	Base-A-A-B-C-C-C-Tip
60.96 (200)	Base-A-C-C-C-D-Tip
64.01 (210)	Base-A-A-C-C-C-D-Tip
67.06 (220)	Base-A-A-C-C-D-D-Tip
70.10 (230)	Base-A-B-C-C-D-D-Tip
73.15 (240)	Base-A-B-C-C-A-D-D-Tip
76.20 (250)	Base-A-A-C-C-C-D-D-Tip
79.25 (260)	Base-A-B-C-C-C-D-D-Tip
82.30 (270)	Base-A-B-C-C-A-C-D-D-Tip

Base = 762 m (25'), Tip = 10.7 m (35')  
 Inserts: A = 3.05 m (10'), B = 6.10 m (20'),  
 C = 9.14 m (30'), D = 12.19 m (40')

## Jib Component Chart

Jib length m (ft)	Jib arrangement
12.19 (40)	Base-A-Tip
18.29 (60)	Base-A-B-Tip
24.38 (80)	Base-A-B-B-Tip
30.48 (100)	Base-A-B-B-B-Tip

Base = 4.57 m (15'), Tip = 4.57 m (15')  
 Insert: A = 3.05 m (10'), B = 6.10 m (20')

# Boom Lifting Capacities (Standard)

## Rated Loads in Metric Tons for 360° Working Area (standard)

Unit: metric ton

Boom length m (ft) Operating radius m (ft)	18.29 (60)	21.34 (70)	24.38 (80)	27.43 (90)	30.48 (100)	33.53 (110)	36.58 (120)	39.62 (130)	42.67 (140)	45.72 (150)	48.77 (160)	Boom length m (ft) Operating radius m (ft)
5 (16-5)	150.0											5 (16-5)
6 (19-8)	140.0	128.1	116.8									6 (19-8)
7 (23-0)	123.6	121.7	111.5	102.5	94.4							7 (23-0)
8 (26-3)	99.1	98.8	98.7	96.2	90.7	83.8	77.8					8 (26-3)
9 (29-6)	82.5	82.3	82.2	82.0	81.8	78.8	75.2	69.6				9 (29-6)
10 (32-10)	70.5	70.3	70.2	70.1	69.9	69.8	69.2	66.5	62.3	57.8		10 (32-10)
12 (39-4)	54.6	54.3	54.2	54.0	53.8	53.7	53.5	53.3	53.2	52.2	49.6	12 (39-4)
14 (45-11)	44.5	44.2	44.0	43.9	43.6	43.5	43.2	43.1	42.9	42.7	42.6	14 (45-11)
16 (52-6)	37.5	37.1	37.0	36.8	36.5	36.4	36.1	35.9	35.8	35.6	35.5	16 (52-6)
18 (59-0)		32.0	31.8	31.6	31.3	31.1	30.8	30.7	30.6	30.4	30.2	18 (59-0)
20 (65-7)			27.8	27.6	27.3	27.1	26.8	26.7	26.5	26.3	26.2	20 (65-7)
22 (72-2)			24.7	24.4	24.2	24.0	23.7	23.5	23.4	23.1	23.0	22 (72-2)
24 (78-9)				21.9	21.6	21.4	21.1	20.9	20.8	20.6	20.4	24 (78-9)
26 (85-4)					19.5	19.3	19.0	18.8	18.7	18.4	18.2	26 (85-4)
28 (91-10)						17.5	17.2	17.0	16.9	16.6	16.4	28 (91-10)
30 (98-5)						16.1	15.7	15.5	15.4	15.1	14.9	30 (98-5)
32 (105-0)							14.4	14.2	14.0	13.8	13.6	32 (105-0)
34 (111-7)								13.1	12.9	12.7	12.5	34 (111-7)
36 (118-1)									11.9	11.7	11.5	36 (118-1)
38 (124-8)									11.1	10.8	10.6	38 (124-8)
40 (131-3)										10.1	9.8	40 (131-3)
42 (137-10)											9.1	42 (137-10)

Unit: metric ton

Boom length m (ft) Operating radius m (ft)	51.82 (170)	54.86 (180)	57.91 (190)	60.95 (200)	64.01 (210)	67.06 (220)	70.10 (230)	73.15 (240)	76.20 (250)	79.25 (260)	82.30 (270)	Boom length m (ft) Operating radius m (ft)
12 (39-4)	46.9	43.5	40.0									12 (39-4)
14 (45-11)	41.8	40.3	38.1	37.0	36.2	33.5	30.3					14 (45-11)
16 (52-6)	35.2	35.1	33.8	35.6	35.2	32.7	29.6	27.1	25.0	22.8	20.3	16 (52-6)
18 (59-1)	30.0	29.8	29.6	30.3	30.1	30.1	28.8	26.4	24.4	22.1	19.7	18 (59-1)
20 (65-7)	25.9	25.7	25.5	26.2	25.9	25.9	25.9	25.7	23.8	21.6	19.2	20 (65-7)
22 (72-2)	22.8	22.5	22.3	22.9	22.6	22.7	22.6	22.4	22.3	21.0	18.6	22 (72-2)
24 (78-9)	20.2	19.9	19.7	20.2	20.0	20.0	20.0	19.7	19.6	19.4	18.0	24 (78-9)
26 (85-4)	18.0	17.7	17.6	18.0	17.8	17.8	17.7	17.5	17.4	17.2	16.7	26 (85-4)
28 (91-10)	16.2	15.9	15.8	16.2	15.9	15.9	15.9	15.6	15.5	15.3	15.2	28 (91-10)
30 (98-5)	14.7	14.4	14.3	14.6	14.3	14.3	14.3	14.0	13.9	13.7	13.6	30 (98-5)
32 (105-0)	13.4	13.1	12.9	13.2	13.0	13.0	12.9	12.6	12.5	12.3	12.3	32 (105-0)
34 (111-7)	12.2	11.9	11.8	12.0	11.8	11.8	11.7	11.4	11.3	11.1	11.1	34 (111-7)
36 (118-1)	11.2	10.9	10.8	11.0	10.7	10.7	10.7	10.4	10.3	10.1	10.0	36 (118-1)
38 (124-8)	10.3	10.1	9.9	10.1	9.8	9.8	9.8	9.5	9.3	9.1	9.1	38 (124-8)
40 (131-3)	9.6	9.3	9.1	9.3	9.0	9.0	8.9	8.6	8.5	8.3	8.2	40 (131-3)
42 (137-10)	8.9	8.6	8.4	8.5	8.2	8.2	8.2	7.9	7.8	7.6	7.5	42 (137-10)
44 (144-4)	8.2	7.9	7.7	7.9	7.6	7.6	7.5	7.2	7.1	6.9	6.8	44 (144-4)
46 (150-11)	7.7	7.4	7.2	7.3	7.0	7.0	6.9	6.6	6.5	6.2	6.1	46 (150-11)
48 (157-6)		6.9	6.6	6.7	6.4	6.4	6.4	6.0	5.9	5.6	5.4	48 (157-6)
50 (164-1)			6.2	6.2	5.9	5.9	5.9	5.5	5.3	5.0	4.9	50 (164-1)
52 (170-7)				5.8	5.4	5.4	5.3	4.9	4.7	4.5	4.3	52 (170-7)
54 (177-0)				5.4	5.0	5.0	4.8	4.4	4.2	4.0	3.8	54 (177-0)
56 (183-9)					4.5	4.5	4.4	4.0	3.8	3.5	3.4	56 (183-9)
58 (190-3)						4.1	4.0	3.6	3.4	3.1	2.9	58 (190-3)
60 (196-10)							3.6	3.2	3.0	2.7	2.5	60 (196-10)
62 (203-5)							3.2	2.8	2.6	2.4	2.2	62 (203-5)

# Boom Lifting Capacities (with carbody counterweights and an additional counterweight)

## Rated Loads in Metric Tons for 360° Working Area (with carbody counterweights and an additional counterweight)

Unit: metric ton

Boom length m (ft) Operating radius m (ft-in)	18.29 (60)	21.34 (70)	24.38 (80)	27.43 (90)	30.48 (100)	33.53 (110)	36.58 (120)	39.62 (130)	42.67 (140)	45.72 (150)	48.77 (160)	Boom length m (ft) Operating radius m (ft-in)
5 (16-5)	150.0											5 (16-5)
6 (19-8)	140.0	128.1	116.8									6 (19-8)
7 (23-0)	123.6	121.7	111.5	102.5	94.4							7 (23-0)
8 (26-3)	104.8	104.6	102.3	96.2	90.7	83.8	77.8					8 (26-3)
9 (29-6)	90.0	90.4	89.8	87.1	82.7	79.5	75.2	69.6				9 (29-6)
10 (32-10)	78.4	79.3	79.1	78.5	75.6	72.7	69.4	66.5	62.3	57.8		10 (32-10)
12 (39-4)	61.1	62.9	63.4	63.3	62.6	61.8	59.3	56.8	54.7	52.2	50.2	12 (39-4)
14 (45-11)	48.5	51.2	52.3	52.6	52.3	51.8	51.1	49.5	47.7	45.5	43.8	14 (45-11)
16 (52-6)	38.4	42.1	43.9	44.4	44.2	44.0	43.7	43.3	42.1	40.2	38.7	16 (52-6)
18 (59-0)		34.6	37.1	38.2	37.9	37.7	37.5	37.4	37.1	36.0	34.7	18 (59-0)
20 (65-7)			31.3	32.9	33.1	32.9	32.7	32.5	32.3	32.2	31.2	20 (65-7)
22 (72-2)			26.0	28.3	29.3	29.1	28.9	28.7	28.5	28.4	28.1	22 (72-2)
24 (78-9)				24.1	25.5	26.1	25.8	25.7	25.4	25.3	25.0	24 (78-9)
26 (85-4)					22.1	23.2	23.3	23.1	22.9	22.7	22.5	26 (85-4)
28 (91-10)						20.3	21.0	21.0	20.8	20.6	20.3	28 (91-10)
30 (98-5)						17.6	18.6	19.1	18.9	18.8	18.5	30 (98-5)
32 (105-0)							16.3	17.1	17.4	17.2	16.9	32 (105-0)
34 (111-7)								15.1	15.7	15.9	15.6	34 (111-7)
36 (118-1)									14.0	14.4	14.4	36 (118-1)
38 (124-8)									12.3	12.9	13.1	38 (124-8)
40 (131-3)										11.5	11.8	40 (131-3)
42 (137-10)											10.5	42 (137-10)

Unit: metric ton

Boom length m (ft) Operating radius m (ft-in)	51.82 (170)	54.86 (180)	57.91 (190)	60.96 (200)	64.01 (210)	67.06 (220)	70.10 (230)	73.15 (240)	76.20 (250)	79.25 (260)	82.30 (270)	Boom length m (ft) Operating radius m (ft-in)
12 (39-4)	46.9	43.5	40.0									12 (39-4)
14 (45-11)	41.8	40.3	38.1	37.0	36.2	33.5	30.3					14 (45-11)
16 (52-6)	36.9	35.6	33.8	35.6	35.2	32.7	29.6	27.1	25.0	22.8	20.3	16 (52-6)
18 (59-1)	33.0	31.8	30.2	32.9	33.7	31.3	28.8	26.4	24.4	22.1	19.7	18 (59-1)
20 (65-7)	29.8	28.7	27.2	29.5	31.8	30.5	27.6	25.7	23.8	21.6	19.2	20 (65-7)
22 (72-2)	27.1	26.0	24.7	26.6	27.9	27.9	26.8	24.6	22.7	21.0	18.6	22 (72-2)
24 (78-9)	24.7	23.8	22.5	24.2	24.7	24.7	24.7	23.9	21.4	19.6	18.0	24 (78-9)
26 (85-4)	22.3	21.8	20.7	22.0	22.1	22.1	22.1	21.8	20.1	18.2	16.9	26 (85-4)
28 (91-10)	20.2	19.9	19.0	20.1	19.9	19.9	19.8	19.6	18.8	17.0	15.7	28 (91-10)
30 (98-5)	18.4	18.1	17.5	18.3	18.0	18.0	18.0	17.7	17.6	15.8	14.6	30 (98-5)
32 (105-0)	16.8	16.5	16.1	16.6	16.4	16.4	16.3	16.1	15.9	14.8	13.5	32 (105-0)
34 (111-7)	15.4	15.1	14.9	15.2	15.0	15.0	14.9	14.6	14.5	13.8	12.5	34 (111-7)
36 (118-1)	14.2	13.9	13.8	14.0	13.7	13.7	13.7	13.4	13.3	12.7	11.5	36 (118-1)
38 (124-8)	13.2	12.9	12.7	12.9	12.6	12.6	12.6	12.3	12.2	11.6	10.4	38 (124-8)
40 (131-3)	12.0	11.9	11.7	11.9	11.6	11.6	11.6	11.3	11.2	10.6	9.7	40 (131-3)
42 (137-10)	10.8	10.8	10.7	11.1	10.8	10.8	10.7	10.4	10.3	9.9	9.0	42 (137-10)
44 (144-4)	9.7	9.8	9.7	10.3	10.0	10.0	9.9	9.6	9.5	9.3	8.5	44 (144-4)
46 (150-11)	8.6	8.8	8.8	9.6	9.3	9.3	9.2	8.9	8.8	8.6	7.8	46 (150-11)
48 (157-6)		7.8	7.9	8.9	8.6	8.6	8.5	8.2	8.1	7.9	7.4	48 (157-6)
50 (164-1)			7.0	8.3	8.0	8.0	7.9	7.6	7.5	7.3	6.8	50 (164-1)
52 (170-7)				7.8	7.5	7.5	7.4	7.1	7.0	6.8	6.3	52 (170-7)
54 (177-0)				7.3	7.0	7.0	6.9	6.6	6.4	6.2	5.8	54 (177-0)
56 (183-9)					6.5	6.5	6.4	6.1	5.9	5.6	5.4	56 (183-9)
58 (190-3)						6.1	6.0	5.6	5.4	5.1	4.9	58 (190-3)
60 (196-10)							5.5	5.2	5.0	4.7	4.5	60 (196-10)
62 (203-5)							5.1	4.7	4.5	4.3	4.1	62 (203-5)
64 (210-0)								4.3	4.1	3.9	3.7	64 (210-0)

# Fixed Jib Lifting Capacities

## Jib Rated Loads in Metric Tons for 360° Working Area

Unit: metric ton

Operating radius m (ft-in)	45.72 m (150') boom								Operating radius m (ft-in)
	12.19 m (40') jib		18.29 m (60') jib		24.38 m (80') jib		30.48 m (100') jib		
	Offset angle								
	10°	30°	10°	30°	10°	30°	10°	30°	
14 (45-11)	5.0								14 (45-11)
16 (52-6)	5.0								16 (52-6)
18 (59-0)	5.0	13.0	12.0						18 (59-0)
20 (65-7)	5.0	13.0	12.0		8.0				20 (65-7)
22 (72-2)	5.0	13.0	12.0	8.0	8.0		4.0		22 (72-2)
24 (78-9)	5.0	13.0	12.0	8.0	8.0		4.0		24 (78-9)
26 (85-4)	5.0	13.0	12.0	8.0	7.8	6.0	4.0		26 (85-4)
28 (91-10)	5.0	12.6	12.0	8.0	7.6	6.0	4.0		28 (91-10)
30 (98-5)	5.0	12.3	12.0	8.0	7.4	6.0	4.0	3.0	30 (98-5)
34 (111-7)	12.7	11.5	11.5	8.0	7.1	6.0	4.0	3.0	34 (111-7)
38 (124-8)	10.8	10.8	10.6	7.6	6.7	5.7	3.7	3.0	38 (124-8)


Operating radius m (ft-in)	57.91 m (190') boom								Operating radius m (ft-in)
	12.19 m (40') jib		18.29 m (60') jib		24.38 m (80') jib		30.48 m (100') jib		
	Offset angle								
	10°	30°	10°	30°	10°	30°	10°	30°	
14 (45-11)									14 (45-11)
16 (52-6)	5.0								16 (52-6)
18 (59-0)	5.0								18 (59-0)
20 (65-7)	5.0	13.0	12.0						20 (65-7)
22 (72-2)	5.0	13.0	12.0		8.0				22 (72-2)
24 (78-9)	5.0	13.0	12.0	8.0	8.0		4.0		24 (78-9)
26 (85-4)	5.0	13.0	12.0	8.0	8.0		4.0		26 (85-4)
28 (91-10)	5.0	13.0	12.0	8.0	8.0	6.0	4.0		28 (91-10)
30 (98-5)	14.3	13.0	12.0	8.0	8.0	6.0	4.0		30 (98-5)
34 (111-7)	11.8	11.8	11.8	8.0	7.6	6.0	4.0	3.0	34 (111-7)
38 (124-8)	9.9	9.9	9.9	8.0	7.2	6.0	4.0	3.0	38 (124-8)
42 (137-10)	8.4	8.4	8.4	7.7	6.8	5.7	3.9	3.0	42 (137-10)
46 (150-11)	7.2	7.2	7.2	7.2	6.4	5.4	3.6	2.9	46 (150-11)
50 (164-1)	6.2	6.2	6.2	6.2	6.0	5.1	3.3	2.8	50 (164-1)

Operating radius m (ft-in)	73.15 m (240') boom								Operating radius m (ft-in)
	12.19 m (40') jib		18.29 m (60') jib		24.38 m (80') jib		30.48 m (100') jib		
	Offset angle								
	10°	30°	10°	30°	10°	30°	10°	30°	
18 (59-0)	5.0								18 (59-0)
20 (65-7)	5.0								20 (65-7)
22 (72-2)	5.0	13.0	12.0						22 (72-2)
24 (78-9)	5.0	13.0	12.0		8.0				24 (78-9)
26 (85-4)	5.0	13.0	12.0		8.0		4.0		26 (85-4)
28 (91-10)	5.0	13.0	12.0	8.0	8.0		4.0		28 (91-10)
30 (98-5)	14.0	13.0	12.0	8.0	8.0		4.0		30 (98-5)
34 (111-7)	11.4	11.4	11.4	8.0	8.0	6.0	4.0		34 (111-7)
38 (124-8)	9.5	9.5	9.5	8.0	7.7	6.0	4.0	3.0	38 (124-8)
42 (137-10)	7.9	7.9	7.9	7.8	7.4	6.0	4.0	3.0	42 (137-10)
46 (150-11)	6.6	6.6	6.6	6.6	6.6	5.6	4.0	3.0	46 (150-11)
50 (164-1)	5.5	5.5	5.5	5.5	5.5	5.1	3.7	3.0	50 (164-1)
54 (177-0)	4.4	4.4	4.4	4.4	4.4	4.4	3.5	2.8	54 (177-0)
58 (190-3)	3.6	3.6	3.6	3.6	3.6	3.6	3.2	2.7	58 (190-3)
62 (203-5)	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.5	62 (203-5)

Note: This chart presents rated jib loads for three possible boom lengths. Data for boom lengths from 150 to 240 feet at 10-foot intervals is available upon request

# Luffing Jib Lifting Capacities

## Working Ranges



## Boom Component Chart

Boom length meters (ft)	Boom arrangement
35.35 (116)	Base-B'A-C-Cap
38.40 (126)	Base-B'B-C-Cap
41.44 (136)	Base-B'C-C-Cap
44.49 (146)	Base-B'A-C-C-Cap
47.54 (156)	Base-B'B-C-C-Cap
50.59 (166)	Base-B'A-B-C-C-Cap
53.64 (176)	Base-B'A-A-B-C-C-Cap

Base = 7.62 m (25'), Cap = 9.14 m (30')  
 Inserts: B = 6.10 m (20'), B' = 6.10 m (20')  
 A = 3.05 m (10'), C = 9.14 m (30')

**Note:** B' 6.10 m (20') Boom is for luffing jib use only.

## Jib Component Chart

Boom length meters (ft)	Boom arrangement
27.43 (90)	Base-C-Tip
30.48 (100)	Base-A-C-Tip
33.53 (110)	Base-B-C-Tip
36.58 (120)	Base-C-C-Tip
39.62 (130)	Base-A-C-C-Tip
42.67 (140)	Base-B-C-C-Tip
45.72 (150)	Base-A-B-C-C-Tip

Base = 9.14 m (30'), Tip = 9.14 m (30')  
 Inserts: A = 3.05 m (10'), B = 6.10 m (20')  
 C = 9.14 m (30')

## Luffing Jib Rated Loads in Metric Tons for 360° Working Area


Unit: metric ton

Boom length m (ft)	35 35-47 54 (116-156)	38 38-50 59 (118-166)	38 40 53 46 (126-176)	41 44 53 64 (136-176)	44 49 53 64 (146-176)	47 54 53 64 (156-176)	50 59 53 64 (166-176)	Boom length m (ft)
Jib length m (ft)	27.43 (90)	30.48 (100)	33.53 (110)	36.58 (120)	39.62 (130)	42.67 (140)	45.72 (150)	Jib length m (ft)
Operating radius m (ft)								Operating radius m (ft)
13 (42-8)	13.1m x 20.0							13 (42-8)
14 (45-11)	20.0		14.2m x 20.0					14 (45-11)
15 (49-3)	15.8m x 20.0		15.8m x 20.0		15.8m x 19.3			15 (49-3)
16 (52-6)	19.5		19.5		18.9		16.4m x 17.8	
18 (59-0)	17.7		17.7		17.7		17.1	
20 (65-7)	16.1		16.1		16.1		16.1	
22 (72-2)	14.7		14.7		14.7		14.7	
24 (78-9)	13.4		13.4		13.4		13.4	
26 (85-4)	12.1		12.1		12.1		12.1	
28 (91-10)	10.9		10.9		10.9		10.9	
30 (98-5)	28m x 10.8		9.8		9.8		9.8	
32 (105-0)			30.9m x 9.4		9.0		9.0	
34 (111-7)					33.7m x 8.4		8.3	
36 (118-1)							7.6	
38 (124-8)					36.4 x 7.5		7.0	
40 (131-3)							39.2 x 6.7	
42 (137-10)							6.5	
44 (144-4)							6.0	
45 (147-8)							5.6	
							44.7m x 5.4	
							45 (147-8)	



# Clamshell

## 10.5 Metric Ton (23,148 lb) Rated Load 24.37 m Maximum Boom



### Rated Loads in kg (standard)

Boom length Operating radius m (ft-in)	18.29 (60) boom	21.34 (70) boom	24.38 (80) boom	27.43 (90) boom
10.0 (32-10)	10,500			
12.0 (39-4)	10,500	10,500		
14.0 (45-11)	10,500	10,500	10,500	
16.0 (52-6)	10,500	10,500	10,500	10,500
18.0 (59-1)		10,500	10,500	10,500
20.0 (65-7)			10,500	10,500
22.0 (72-2)				10,500
24.0 (78-9)				10,500

**Note:** Table shows loads using standard 26mm wire and standard drums.

### Rated Loads in kg (optional)

Boom length Operating radius m (ft-in)	18.29 (60) boom	21.34 (70) boom	24.38 (80) boom	27.43 (90) boom
10.0 (32-10)	12,500			
12.0 (39-4)	12,500	12,500		
14.0 (45-11)	12,500	12,500	12,500	
16.0 (52-6)	12,500	12,500	12,500	12,500
18.0 (59-1)		12,500	12,500	12,500
20.0 (65-7)			12,500	12,500
22.0 (72-2)				12,500
24.0 (78-9)				12,500

**Note:** Table shows loads using optional 28mm wire and drums.

Above ratings are combined weights of bucket and material. Clamshell ratings shown also apply to grapple and all other material handling buckets except dragline. For clamshell operations, the weight of bucket is considered a part of the load and the total weight of bucket plus contents must not exceed the corresponding rating shown.




- Limit on clamshell rating ..... 10,500 kg (23,100 lb)
- Limit on clamshell rating (using 28mm dia. wire rope—opt.)...  
..... 12,500 kg (27,600 lb)
- Maximum allowable bucket ..... 3.0 m<sup>3</sup> (3.9 cu yd)
- Maximum allowable bucket weight ..... 6,000 kg (13,200 lb)

**Note:**

To select the bucket size best suited for your application, use the following formula: refer to the above charts to obtain clamshell capacity in kg. Clamshell capacity = (cubic meter capacity of bucket) × (weight of material per cubic meter) + (weight of specific clamshell bucket).

# Upgraded lifting capacity

The following graphs show how hoisting capacity can be increased, using the 20 metric ton carbody counterweight and additional 8.3 metric ton counterweight.



Address inquiries to:

## RICON PRIVATE LIMITED

12 Tuas Drive 2 Singapore 638646

Tel: 8622401 Fax: 8615828

E-mail: sales@ricon.com.sg

**NOTE:** Due to our policy of continual product improvement, all designs and specifications are subject to change without advance notice.



## KOBE STEEL, LTD.

CONSTRUCTION MACHINERY DIVISION

27-8, Jingumae 6-chome, Shibuya-ku, Tokyo, 150 JAPAN

Tel: (03) 3797-7021/Fax: (03) 3797-7072

910503TF Printed in Japan